

Item No.	Prop	Throttle	Voltage (V)	Current (A)	Input Power (W)	RPM	Torque (N*m)	Output Power (W)	Thrust (G)	Efficiency	Efficiency (G/W)	Operating Temperature (°C)
电机型号	螺旋桨	油门点	电压(V)	电流(A)	输入功率(W)	转速(rpm)	转矩(N.m)	输出功率(W)	拉力(g)	效率(%)	力效	电机温度
AT2826-KV900	APC 12*6	40%	15.11	11.43	172.61	6258.39	0.19	123.09	1116.70	71.31	6.47	98°C
		45%	15.07	13.63	205.47	6633.85	0.21	148.25	1271.59	72.15	6.19	
		50%	15.03	15.68	235.81	6949.92	0.24	171.53	1406.48	72.74	5.96	
		55%	15.00	17.71	265.69	7263.24	0.26	195.00	1528.27	73.39	5.75	
		60%	14.97	19.84	296.86	7508.89	0.28	220.72	1669.83	74.35	5.63	
		65%	14.93	21.92	327.20	7782.08	0.30	244.71	1779.08	74.79	5.44	
		70%	14.88	24.53	365.16	8080.49	0.32	272.99	1932.72	74.76	5.29	
		75%	14.82	28.51	422.43	8467.85	0.37	328.35	2154.77	77.73	5.10	
		80%	14.74	33.36	491.67	8879.01	0.41	382.17	2396.62	77.73	4.87	
		90%	14.58	42.72	622.90	9556.38	0.49	489.37	2810.38	78.56	4.51	
	100%	14.50	47.28	685.84	9797.65	0.52	537.49	2991.61	78.37	4.36		
	APC 13*6.5	40%	15.10	12.19	183.97	5610.52	0.22	127.17	1216.18	69.12	6.61	HOT
		45%	15.05	14.84	223.29	6011.51	0.25	155.59	1387.86	69.68	6.22	
		50%	15.01	17.32	259.98	6344.58	0.28	183.12	1541.34	70.44	5.93	
		55%	14.97	19.81	296.47	6637.56	0.30	211.17	1698.32	71.23	5.73	
		60%	14.91	22.84	340.67	6947.69	0.34	245.73	1884.89	72.13	5.53	
		65%	14.85	26.58	394.75	7297.07	0.38	287.34	2090.62	72.79	5.30	
		70%	14.79	30.38	449.24	7656.17	0.42	332.78	2291.01	74.08	5.10	
		75%	14.71	34.95	514.23	8000.00	0.46	382.20	2513.40	74.32	4.89	
		80%	14.63	39.79	582.14	8324.74	0.51	444.57	2744.52	76.37	4.71	
		90%	14.44	51.45	743.02	8953.17	0.59	556.66	3212.16	74.92	4.32	
	100%	14.35	57.16	820.02	9182.58	0.64	612.41	3409.39	74.68	4.16		
	APC 14*7	40%	11.36	8.96	101.76	4169.86	0.16	68.44	825.57	67.26	8.11	87°C
		45%	11.33	10.62	120.33	4435.38	0.18	83.10	943.13	69.05	7.84	
		50%	11.29	12.63	142.61	4708.99	0.20	99.64	1060.66	69.87	7.44	
		55%	11.26	14.76	166.16	4951.92	0.23	117.89	1189.08	70.95	7.16	
		60%	11.23	16.66	187.02	5172.64	0.25	135.07	1297.90	72.23	6.94	
		65%	11.18	19.33	216.15	5456.57	0.28	158.70	1443.73	73.42	6.68	
		70%	11.13	22.74	252.95	5738.28	0.31	188.21	1623.54	74.40	6.42	
		75%	11.06	26.62	294.42	6066.85	0.35	221.45	1797.82	75.22	6.11	
80%		10.99	30.69	337.39	6338.34	0.38	255.34	1971.15	75.68	5.84		
90%		10.82	41.07	444.58	6905.96	0.47	336.76	2349.68	75.75	5.29		
100%	10.77	44.15	475.59	7048.30	0.49	360.30	2446.53	75.76	5.14			

APC 15*8	40%	11.34	8.92	101.10	3744.91	0.19	73.74	921.00	72.94	9.11	HOT
	45%	11.31	10.56	119.50	3948.61	0.21	86.82	1030.20	72.65	8.62	
	50%	11.28	12.69	143.14	4182.22	0.24	104.76	1168.15	73.18	8.16	
	55%	11.23	15.35	172.38	4465.08	0.27	125.64	1327.61	72.89	7.70	
	60%	11.17	19.17	214.08	4804.98	0.31	156.81	1534.13	73.25	7.17	
	65%	11.10	23.09	256.38	5095.37	0.35	188.66	1730.10	73.59	6.75	
	70%	11.04	27.02	298.20	5371.67	0.39	220.98	1914.30	74.10	6.42	
	75%	10.95	32.45	355.28	5650.03	0.44	260.74	2139.92	73.39	6.02	
	80%	10.88	36.74	399.67	5879.15	0.48	293.14	2316.51	73.35	5.80	
	90%	10.71	46.75	500.90	6276.86	0.56	366.20	2680.34	73.11	5.35	
	100%	10.63	51.81	550.80	6424.32	0.59	398.10	2843.58	72.28	5.16	